

**FLOORING
PRODUCTS**

Self-declaration that the named products comply with the requirements for flooring products as per BREEAM-NOR's chapter HEA 02

This form must be filled out by the MANUFACTURER of flooring products according to NS-EN 13813. The requirements apply to the following types of flooring products:

- Screed material
- Floor screeds

Approved emission certificates are M1¹, EC1² or SINTEF Technical Approval.

You can use this declaration to confirm the absence of regulated wood preservatives, if your certification/documentation does not already prove it.

Connect the emission certificate to the product in goBIM.

¹ Approved performance standard NS-EN 15251:2007, Annex C

² Approved performance standard GEV Emissioncode

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR 2016. If in doubt, the manufacturer should consult own internal and external experts. **Providing incorrect and misleading information can have legal consequences. Once filled-out, the form must be signed by a legally responsible person for the manufacturer, such as a technical director or a managing director.**

MANUFACTURER:

PRODUCT TRADE NAME:

PRODUCT ID:

The following is hereby confirmed by the manufacturer:

1. The product is in accordance with product standard: NS-EN 13813.
2. The product has undergone an emission test³ which shows that its emissions are below the values⁴ shown in BREEAM-NOR 2016 "Table 15" according to the intended use of the product.

Table 15: Emission limits for all product categories – Conversion table

Emission	Wall		Floor/ceiling		Sealants	
	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3$	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3$	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3$
TVOC 28d	200	417	200	160	4260	60
Formaldehyde 3d*	24	50	62.5	50	3550	50
Formaldehyde 28d*	50	104	50	40	710	10
Carcinogenic	5	10	5	4	71	1

³Documentation (test in acc. with approved standard) can be requested if required.

⁴Show accordance with units $\mu\text{g}/\text{m}^3$ or $\mu\text{g}/\text{m}^2\text{h}$

*Emission levels for 3 or 28 days can be used as a basis for documenting compliance.

3. The emission test has been performed in accordance with the following approved standards ISO 16000-9 together with ISO 16000-6 (volatile organic compounds) and ISO 16000-3 (formaldehyde). Test and calculation shall be carried out according to EN 16516.

Legally responsible:

Position:

Date:

Signature: